


Transformer

Material Data Sheet

Product Class:	EP7 SMD B78417AxxxxAxxx	
Date	17.10.2011	
IMDS ID if available		
Version:	03	

Product part (IMDS: semi component)	Material Class (IMDS: Material)	Material (Classification) VDA 231	Substance	TMPS** [wt%]	CAS if applicable	typical mass of material [wt-%]	Traces see 1)
Active Part	Ceramic	4B	Manganese Zinc Ferrite	100	1264549-7	70.8	
	Heavy Metal	1C	Cu	100	7440-50-8	12.8	
	Elastomer	2B	Polyurethane (PUR)	100	9009-54-5	0.7	
Encapsulation	Thermoplastic	2A	Glass fiber	50-65	65997-17-3	13.4	
			Phenolic resin	35-50	9003-35-4		
	Duromer	2C	Epoxy resin (EP)	100	25928-94-3	0.2	
	Woven material	3A	Polyester	100	113669-97-9	0.5	
Termination	Heavy Metal	1C	Cu	94	7440-50-8	1.4	
			Sn	6	7440-31-5		
	Heavy Metal	1C	Ni	100	7440-02-0		x
	Heavy Metal	1C	Sn	100	7440-31-5	0.2	
Sum in total:						100	



Size W x L x H [max. in mm]	Weight [approx. in g]	Part Numbers	REMARK:	Size W x L x H [max. in mm]	Weight [approx. in g]	Part Numbers
9.78x9.0x10.9	1.93	B78417A9423A003;T6945		8.9x9.6x10.9	2.0	B78417A1967A003;T2360
12.9x11.0x9.2	2.0	B78417A1637A003;X587		8.9x9.6x10.9	2.0	B78417A1973A003;T2462
8.9x9.6x10.9	2.0	B78417A1698A003;Y112		8.9x9.6x11.4	2.0	B78417A1977A003;T2350
7.8x8.9x10.8	2.0	B78417A1706A003;Y149		8.9x9.6x10.9	2.0	B78417A1982A003;T2631
12.3x10.3x6.1	2.0	B78417A1717A003;Y208		8.9x9.6x10.9	2.0	B78417A1987A003;T2119
8.9x7.8x10.8	2.0	B78417A1744A003;Y442		8.9x9.6x10.9	2.0	B78417A1993A003;T3158
10.0x8.9x10.8	2.0	B78417A1761A003;Y333		8.9x10.0x10.9	2.0	B78417A2021A003;T3670
10.0x8.9x10.8	2.0	B78417A1762A003;Y334		8.9x9.6x10.9	2.0	B78417A2035A003;T2802
10.0x9.0x10.9	2.0	B78417A1763A003;Y335		13.0x10.2x8.9	2.2	B78417A2053A003;T2334
8.9x7.8x10.8	2.0	B78417A1764A003;Y339		8.9x10.0x10.9	2.0	B78417A2056A003;T3567
8.9x9.6x10.9	2.0	B78417A1765A003;Y363		8.9x10.0x10.9	2.0	B78417A2057A003;T3568
8.9x7.8x10.8	2.0	B78417A1822A003;Y705		8.9x9.6x10.9	2.0	B78417A2069A003;T4875
8.9x10.0x11.2	2.0	B78417A1833A003;T0562		13.1x10.8x9.1	2.2	B78417A2093A003;T4247
8.9x9.6x10.9	2.0	B78417A1838A003;T0792		13.0x10.1x8.9	2.2	B78417A2104A003;T5173
8.9x9.6x10.9	2.0	B78417A1847A003;T0989		8.9x9.6x10.9	2.0	B78417A2134A003;T6599
7.8x9.6x10.9	2.0	B78417A1851A003;T1012		13.0x10.1x8.9	2.2	B78417A2136A003;T6406
10.0x8.9x10.9	2.0	B78417A1859A003;T0880		13.0x10.1x10.5	2.2	B78417A2137A003;T6727
8.9x9.6x10.9	2.0	B78417A1907A003;T0483		9.6x9.8x11.4	2.0	B78417A2145A003;T6858
8.9x9.6x10.9	2.0	B78417A1922A003;T2032		14.0x11.0x9.2	1.7	B78417A6760A003;Y033
8.9x9.6x10.9	2.0	B78417A1937A003;T2075		10.0x9.2x10.9	2.0	B78417A6915A003;T0574
9.2x10.0x12.2	2.0	B78417A1939A003;T0729		14.0x9.9x9.2	2.1	B78417A7067A003;T1170
9.0x9.6x10.9	2.0	B78417A1948A003;T1865		8.9x10.0x10.9	2.0	B78417A7187A003;T1450
8.9x9.6x10.9	2.0	B78417A1958A003;T2322		8.9x10.0x10.9	1.9	B78417A7335A003;T1674
9.2x9.6x10.9	2.1	B78417A8205A003;T4005		9.0x8.5x10.9	2.0	B78417A7682A003;T2632
8.9x9.6x10.9	2.0	B78417A8231A003;T4177		9.0x10.0x10.9	2.0	B78417A8207A003;T4093
9.0x9.6x10.9	2.0	B78417A8426A003;T4414		9.2x9.6x10.9	2.0	B78417A8232A003;T4178
9.0x9.6x10.9	2.0	B78417A8427A003;T4415		9.0x9.6x10.9	2.0	B78417A8428A003;T4416
9.2x9.6x10.9	2.0	B78417A8497A003;T4864		9.2x9.6x10.9	1.9	B78417A8563A003;T5053
8.9x9.6x10.9	2.0	B78417A8878A003;T5565		13.1x10.2x9.0	2.0	B78417A8583A003;T4642
9.2x9.8x13.0	2.2	B78417A8928A003;T5598		9.2x9.8x13.0	2.0	B78417A9045A003;T6185
8.9x9.6x10.9	2.0	B78417A9220A003;T6755		8.9x9.6x10.9	2.0	B78417A9205A003;T6653
8.9x9.6x10.9	2.0	B78417A9322A003;T6831		12.7x10.2x10.5	1.7	B78417A2162A003;T6965

Not part of a Product Class

Contact	Dr. Johann Reindl, MAG EPQM	Important remarks: 1) The declaration limit is 0.1% as defined by IEC PAS 61906. Traces are product parts, substances etc. that are below a percentage of 0.1 % by weight, if not otherwise regulated 2) This Material Data Sheet contains typical values of the respective products set forth herein. We expressly point out that all values and statements contained herein are based on our best present knowledge and cannot be regarded as binding statements or binding product specifications, unless otherwise explicitly agreed in writing. EPCOS AG AND ITS AFFILIATES HEREBY EXPRESSLY DISCLAIM ANY REPRESENTATION OR WARRANTY, WHETHER EXPRESS, IMPLIED OR STATUTORY, WITH REGARD TO THE STATEMENTS AND VALUES CONTAINED HEREIN, INCLUDING BUT NOT LIMITED TO ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PURPOSE.
Division	EPCOS AG, Magnetics Business Group (MAG)	
Address	Anzinger Str. 13, 81671 Munich	
	Tel: +49 89 636 29181 mailto: johann.reindl@epcos.com	
*) others: (not declarable or prohibited substances acc. GADSL) **) typical mass percentage of substance		

The products set forth herein are "RoHS-compatible". RoHS-compatible means that products are compatible with the requirements according to Art. 4 (substance restrictions) of Directive 2011/65/EU of the European Parliament and of the Council of June 8th, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

RoHS - Exemptions for the Product Class / Product according to Annex III: (valid not valid)

- no exemptions:
- Exemption 6 (a): Lead as an alloying element in steel for machining purposes and in galvanized steel containing up to 0,35 % lead by weight;
- Exemption 6 (b): Lead as an alloying element in aluminium containing up to 0,4 % lead by weight;
- Exemption 6 (c): Copper alloy containing up to 4 % lead by weight;
- Exemption 7 (a): Lead in high melting temperature type solder (i.e. lead-based alloys containing 85 % by weight or more lead);
- Exemption 7 (c)-I: Electrical and electronic components containing lead in a glass or ceramic other than dielectric ceramic in capacitors, e.g. piezoelectronic devices, or in a glass or ceramic matrix compound;
- Exemption 7 (c)-II: Lead in dielectric ceramic in capacitors for a rated voltage of 125 V AC or 250 V DC or higher;
- Exemption 7 (c)-III: Lead in dielectric ceramic in capacitors for a rated voltage of less than 125 V AC or 250 V DC;
- Exemption 15: Lead in solders to complete a viable electrical connection between semiconductor die and carrier within integrated circuit Flip Chip packages;
- Other Exemption than above